

WHEEL-END ACCESSORIES & TOOLS

HUBODOMETERS

Hubodometers from Amsted Seals® are durable and reliable, helping you accurately track mileage for on-time maintenance, warranties and leases. Choose from analog or electronic hubodometers, available to fit a wide range of tire sizes.



ANALOG

FEATURES

- Popular compact size 3" diameter (7.6cm)
- Features an industry standard ½" – 20 mounting stud
- Hermetically sealed with inert gas and double O-ring protection
- Die cast zinc case; oil impregnated bronze bearings; hardened steel shaft
- Records every revolution in both directions
- Unique counterbalance design
- Fully mechanical with acetal resin gear, pinions and wheel

BENEFITS

- Ensures airtight, tamperproof, waterproof, sealed enclosure
- Most durable unit on market
- Reduces inventory
- Eliminates orbiting and provides precision accuracy
- No calibration, tampering, or batteries

ELECTRONIC

FEATURES

- One model fits any tire application
- Can be programmed in miles or kilometers
- Secure lockout feature
- Mileage can be preset
- Separate trip and lifetime totals
- Can be used for acreage or hectares

BENEFITS

- Allows for a perfect match to any tire size
- Reduces inventory requirements
- Eliminates expensive calibration machines, readers, and complexity
- Changes to the unit's set-up can be permanently disabled
- Eliminates waiting for a hubodometer from the factory
- Simplifies record keeping


PROGRAMMING TOOL & INSTRUCTIONS INCLUDED

WHEEL-END ACCESSORIES & TOOLS


HUBODOMETERS INTERCHANGE

ELECTRONIC HUBODOMETERS							
Amsted Seals®		Veeder-Root			STEMCO		
47000		RT1000-000			600-9999		
ANALOG HUBODOMETERS							
Tire Size	Tread Size	Miles			Kilometers		
		Amsted Seals®	Veeder-Root	STEMCO	Amsted Seals®	Veeder-Root	STEMCO
10 x 22	Extra High	46468M	777717-465	650-0581	46294K	777727-294	650-0526
11 x 24.5	Extra High	46468M	777717-465	650-0581	46294K	777727-294	650-0526
11 x 22	Standard	46468M	777717-465	650-0583	46294K	777727-294	650-0528
12 x 24.5	Standard	46468M	777717-465	650-0583	46294K	777727-294	650-0528
10 x 20	High Tread	46490M	777717-490	650-0587	46308K	777727-306	650-0532
11 x 22.5	High Tread	46490M	777717-490	650-0587	46308K	777727-306	650-0532
10 x 20R	Standard	46500M	777717-500	650-0598	46311K	777727-310	650-0537
11 x 22.5	Standard	46500M	777717-500	650-0598	46311K	777727-310	650-0537
285/75R-24.5	Standard	46500M	777717-500	650-0601	46311K	777727-310	650-0539
9 x 20	High Tread	46500M	777717-500	650-0601	46311K	777727-310	650-0539
10 x 22.5	High Tread	46500M	777717-500	650-0601	46311K	777727-310	650-0539
275/80R-24.5	High Tread	46510M	777717-510	650-0593	46316K	777727-316	650-0532
295/75R-22.5	Standard	46520M	777717-520	650-0610	46326K	777727-326	650-0545
275/80R-22.5	Low Tread	46520M	777717-520	650-0608	46326K	777727-326	650-0545
9 x 20	Standard	46525M	777717-525	650-0608	46326K	777727-326	650-0545
10 x 22.5	Standard	46525M	777717-525	650-0608	46326K	777727-326	650-0545
445/50R22.5	Standard	46525M	777717-525	650-0608	46326K	777727-326	650-0545
HUBODOMETERS BRACKETS							
Amsted Seals®	Description		Bolt Circle	Stud Size	Height	Type	STEMCO
660003	Hubodometer Bracket		6-3/8" – 6-1/2"	1/2" – 9/16"	1-11/16"	A	610-0003
660011	Hubodometer Bracket		7"	5/8"	1-11/16"	A	610-0006
660012	Hubodometer Bracket		7"	3/4"	1-11/16"	A	610-0007
660014	Hubodometer Bracket		5-1/2"	7/16"	4"	A	610-0013
660028	Hubodometer Bracket – 3 Leg		5-1/2"	5/16"	5"	C	610-6028
660084	Hubodometer Bracket – 4 Leg		6-3/4"	5/16"	5"	D	610-0084
660901	Hubodometer Bracket		5-1/2"	5/16"	3-1/2"	A	610-0065
660904	Hubodometer Bracket – Universal		5-1/2" – 7-1/2"	1/2"	1-3/4"	B	610-0011

Hubodometer Bracket Types




A



B



C



D



+1.312.596.5699 • 311 S.Wacker Drive, Suite 5300 Chicago, IL 60606

www.amstedseals.com